



**13.7%**

Module efficiency

**3year**

Quality/Performance Warranty

# S-FLEX · 30-35W

## MWT Mono PERC Flexible Module



- ★ ISO 9001: 2015 Quality Management System
- ★ ISO 45001: 2018 Occupation Health Safety Management System
- ★ ISO 14001: 2015 Environment Management System

### Features

- Light, Thin design**  
0.54kg weight, match various requirements for low-load projects
- High Efficiency And Reliability**  
Busbar-free design increases cell conversion efficiency, more power output can be achieved at low irradiance conditions
- Customizable**  
Customized design for different scenarios
- Convenient Installation**  
Easy installation and convenient transportation with lower cost
- Ultra Flexible**  
Ultra-thin silicon wafers with advanced organic polymer encapsulation materials, minimum bending radius reach 0.30m, fit all kinds of curved surface perfectly
- Lead-free**  
Eco-friendly PV design achieves lead-free MWT module without soldering materials

### Electrical Characteristics at Standard Test Conditions(STC)

Spec/Model	Unit	SPP030QH12S	SPP035QH12S
Max-Power(Pm)	W	30	35
Power Tolerance	W	0~+5	
Max-Power Voltage(Vm)	V	6.6	6.8
Max-Power Current(I <sub>m</sub> )	A	4.56	5.16
Open-Circuit Voltage(Voc)	V	7.9	8.1
Short-Circuit Current(I <sub>sc</sub> )	A	4.84	5.48
Effective Module Efficiency(η <sub>m</sub> )	%	11.8	13.7

STC: AM=1.5, Irradiation 1000W/m<sup>2</sup>, Module Temperature 25°C


### Electrical Characteristics at Nominal Module Operating Temperature (NMOT)

Spec/Model	Unit	SPP030QH12S	SPP035QH12S
Max-Power(Pm)	W	22	26
Max-Power Voltage(Vm)	V	32.5	6.3
Max-Power Current(I <sub>m</sub> )	A	8.09	4.17
Open-Circuit Voltage(Voc)	V	39.6	7.6
Short-Circuit Current(I <sub>sc</sub> )	A	8.61	4.43


NMOT: Irradiation 800W/m<sup>2</sup>, Ambient temperature 20°C, Wind Speed 1m/s

### I-V Curve

I-V Curves of SPP035QH12S at different irradiance



I-V Curves of SPP035QH12S at different cell temperature



### Temperature Coefficient

Nominal Module Operating Temperature	43±2°C
Temperature coefficient of P <sub>max</sub>	-0.36%/°C
Temperature coefficient of Voc	-0.28%/°C
Temperature coefficient of I <sub>sc</sub>	0.06%/°C

### Mechanical Characteristics

Installation Module Dimension (L×W×H)	545mm×363mm×2.5mm
Weight	0.54 kg
Back material	Back Sheet(black/white)
Cell (quantity / material / type / dimensions)	12(2x6)/Mono /166*83mm /φ223mm
Frame	None
Junction box(Protection degree)	None

### Module Size

